

## Dulux PU Lacquer



Product Code	F101-8899
Usage	Dulux PU (Polyurethane) Lacquer is an easy to use, one pack solvent-based gloss lacquer with high quality and excellent durability. Dulux PU (Polyurethane) Lacquer is for use on all types of interior and exterior wooden furnishing including high quality wooden paneling, cane, door partitions and furniture. It provides protection from UV light
Packing	0.91 Litre and 3.64 Litres
FINISHES	Gloss
OTHER PROPERTIES	No Added Lead or Mercury, Pakistan Standards Certified
SURFACE PREPARATION	Scuff the surface thoroughly in the direction of grains with abrasive paper to remove imperfections. Apply 2 coats of Woodcare Wood Sealer. Let it dry. Scuff it with suitable sandpaper, dust off and wipe with petrol and then apply 2-3 coats of Woodcare PU Lacquer.
THINNING RATIO	Brush      Spray      Drying Time
Thinning:	10-15%      20-25%      16 hrs
EQUIPMENT	Brush, Spray Gun Spraying pressure at the gun 3.3-3.7bar (45-55PSI)
CLEANING THINNER	Clean all equipment immediately after use with Mineral Turpentine Thinner
APPLICATION	3-4 full wet single coats should be applied, brush (10- 15%), Spray (20-25%),
FLASH OFF TIME	Approx.10 minutes between coats

**DRYING TIME AT 20°C** Touch dry 4-5 hours  
Hard Dry 16 hours  
**COVERAGE** 11-13m<sup>2</sup>/lit/coat

**SYSTEM INFORMATION**

New

Dulux Wood sealer (F016-2221) – 2 coats

Finish (3-4 coats)

(Previously painted)

Dulux Wood Sealer (F016-2221) – 2 coats

Dulux PU Lacquer (F-101-8899)

## **SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION**

**Flammable.** In case of fire use foam, dry powder, AFFF, CO<sub>2</sub> fire extinguisher. Never use water. No smoking. Keep out of reach of children. Keep away from sources of ignition. Keep container tightly closed and upright to prevent leakage when not in use. **CONTAINS ISOCYANATE**. Ensure good ventilation during drying. Always keep doors and windows fully opened during application and drying. Work only in areas of good ventilation. Irritating to eyes and skin. Do not use on large surface areas inside or small confined spaces. Professional operators may apply to large surface areas inside or in small confined spaces, provided air supplied breathing apparatus is used. Avoid inhalation of Vapors and spray mist. Where practicable, this should be achieved by the use of local exhaust ventilation and good general ventilation. In case of insufficient ventilation during spraying wear suitable respiratory equipment, a suitable cartridge mask should be worn provided the filter is changed regularly. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water keeping eyelids apart and seek medical advice. Contains **COBALT CARBOXYLATE**, May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking. Wear gloves while working. In case of contact with skin, use soap and water or a recognized skin cleaner. Dry sanding, flame cutting and or welding of the dry paint film will give rise to dust and or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. All respiratory equipment must meet an appropriate approved standard. Do not breathe Vapor. If inhalation causes physical discomfort move to fresh air. If discomfort persists or any breathing difficulty occurs, move to fresh air & seek medical advice by showing container label. Harmful if swallowed seek medical advice immediately. Care must be taken when transporting paint. Keep container tightly closed and upright to prevent leakage when not in use. Store in a cool and dry place. In the event of an accident, collect spillage using sand or earth. Do not empty into drains or watercourses. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environment quality regulations. Safety Data Sheet available for professional users on request. This container is only for paint use.

**Contains no added lead or mercury.**